

Handheld fusion splicer

# TYPE-201e Series



TYPE-201e-VS



TYPE-201e-M4

## Lightweight, Tough, Handy



Handy size for working in small spaces



Touch Screen Control Panel



Durable & Rugged

## Specifications

Items		TYPE-201e-VS	TYPE-201e-M4
Optical fibre requirements	Material	Silica glass	
	Profile types	SMF(G.652), MMF(G.651), DSF(G.653), NZDSF(G.655), BIF(G.657)	
	Fibre count	1	1,2,4
	Cladding diameter	125 µm	
	Coating diameter	250µm, 500µm, 900µm	Single fibre coating dia: 250µm, 500µm, 900µm Ribbon fibre thickness: 280-400µm
Standard performance	Applicable cable	Drop cable(2.0mm×3.1 or 2.6mm), Indoor cable(2.0mm×1.6mm)	
	Cleave length	5-10mm	10mm
	Splice loss (typical) *1	SMF:0.05dB, MMF:0.03dB, DSF:0.08dB, NZDSF:0.08dB (With identical Sumitomo fibres)	
	Splice time (typical)	Approx. 11 sec (1C SMF)	Approx. 14 sec (with 4C SMF)
	Heating time (typical)	Approx. 30 sec (with FPS-61-2.6 sleeve)	Approx. 30 sec (with FPS-5 sleeve)
Programs	Splice & heat cycles per battery full charge *2	100 (with BU-12L)	
	Fibre view and magnification	2 CMOS cameras: 72X (ZOOM:216X)	2 CMOS cameras: 36X (ZOOM: 72X)
	Proof test	1.96-2.09N	
	Splice programs	Max. 200	
	Heating programs	Max. 100	
Functions	Splice image capture/Splice data storage	64 images/10,000 splices	
	Onboard user training video	Provided for basic operation and daily maintenance	
	Auto-start	Splice/Heating	
	Automatic arc calibration	Automatically optimizes arc power according to environmental conditions (Auto mode)	
	Automatic fibre count detection	-	Provided
Size / Weight	Remote interactive maintenance	Provided	
	Size	110(W)×140(D)×76(H)mm	
	Weight	620g (without Battery) / 770g (with Battery BU-12S) / 860g (with Battery BU-12L)	
Terminals	Monitor	3.5-inch color monitor with touchscreen	
	USB port	USB2.0 mini-B	
Power supply	Storage media	microSD and microSDHC	
	AC input	100-240V, 50 / 60Hz	
	DC input	10-15V, 4.5A	
Operating condition	Battery pack	Li-ion 11.1V, 3,060mAh(BU-12L)	
	Storage condition	Altitude: 0 - 3,660 m, Temperature: -10 - +50°C, Humidity: 0 - 95% (non-condensing), Wind velocity: up to 15 m/s	
Electrode life *3	Temperature: -40 - +80°C, Humidity: 0 - 95% (non-condensing), Temperature for battery: -20 - +30°C(long term)		
Software updates	3,000 arcs discharges		
Data management	Internet		
		Can be stored, edited and analyzed by dedicated PC software	

\*1 : With Sumitomo identical fibres(in room temperature). Measured by cut-back method relevant to ITU-T and IEC standards.

\*2 : Splice & Heat cycles may vary depending on the battery status and the operating environment.

\*3 : Electrode life may vary depending on the operating environment.

## Environmental Durability\*

	Test details
Shock resistance	Operates normally after being dropped from 76 cm onto one face (bottom).
Water resistance	Equivalent to IPX2 (Operates normally after being exposed to water dripping at 3 mm/min. for at least 2.5 min on each of 4 surfaces tilted at 15°.)
Dust resistance	Equivalent to IP5x (Operates normally after 8 hours in a dust chamber containing dust of particle size 75 µm or below.)

\*Confirms the battery operation in tests carried out by Sumitomo. Does not guarantee that the product is free of faults or damage.

## Basic Accessories

Part name	Part No.	Qty.	TYPE-201e	
			VS	M4
AC adapter	ADC-1340A	1 pc	○	○
Power cord	PC-AC<X>*	1 pc	○	○
Spare electrodes	ER-11	1 pair	○	○
Operating CD manual	-	1 pc	○	○
Carrying case	CCT-201 or CCS-25	1 pc	○	○
USB cable	-	1 pc	○	○
Fibre holders	FHS-025	1 pc	○	-
	FHM-4	1 pc	-	○

\*X=2(USA), 3(EU), 5(UK), 6(AUS), 7(South Africa), 9(INDIA)

At least, the above basic accessories come with splicer main body. Some additional accessories may be or may not be included as a splicer standard kit contents. The standard splicer kit contents varies in each region/country. Please ask details to your nearest distributors.



Carrying case  
CCT-201




Work table  
WT-201



Handy cleaver  
FC-7 / FC-7R series



Hot jacket remover  
JR-6



Available for  
Lynx-Custom Fit™  
Splice-On Connector



Electrode  
ER-11

## Optional Accessories

	Part name	Part No.	TYPE-201e		Description
			VS	M4	
Optional accessories for Splicer	Electrode	ER-11	○	○	Electrodes for TYPE-201 & 201e
	Carrying case	CCT-201	○	○	Hard case
		CCS-25	○	○	Soft case
	Battery pack	BU-12S	○	○	Standard battery
		BU-12L	○	○	Large-capacity battery
	Battery charger	BC-12	○	○	For BU-12S and BU-12L
	AC adapter	ADC-1340A	○	○	For TYPE-201 & 201e main unit and BC-12
	Power cord	PC-AC<X>	○	○	For AC adapter
	Cooling tray	FCT-201	○	○	For cooling fibre protection sleeves
	Alcohol dispenser	HR-3	○	○	Alcohol dispenser
	Neck strap	NS-201	○	○	Neck strap for TYPE-201 & 201e
	Work table	WT-201	○	○	Work table designed exclusively for TYPE-201 & 201e
	Fibre holder	FHS-025	○	○	For φ0.25 mm single fibre
		FHS-09	○	○	For φ0.9 mm single fibre
FHM-2		-	○	For 2-fibre ribbon	
FHM-4		-	○	For 4-fibre ribbon	
FHD-1		○	○	For drop and indoor cables (single fibre)	
Transfer tool	Lynx2-UML-S	○	○	For φ3 mm cord and φ0.9 mm single fibre	
	TRT-201	○	○	To prevent twisting while transferring drop or thin cables	
V-groovecleaning brush	VGT-2	○	○	Brush for cleaning V-groove	
Handheld fibre cleaver	FC-7R-M/F	○	○	Handheld fibre cleaver for single fibre and up to 8-fibre ribbon	
	JR-MO3	○	○	Jacket remover for single fibre	
Jacket remover	JR-6	○	○	Hot jacket remover for ribbon fibre	
	FPS-1	○	○	60 mm sleeve for single fibre	
Fibre protection sleeve	FPS-40	○	○	40 mm sleeve for single fibre	
	FPS-61-2.6	○	○	60mm pre-shrunk sleeve for single fibre	
	FPS-5	○	○	40 mm sleeve for single fibre and up to 8-fibre ribbon	
	FPS-D60	○	○	60 mm sleeve for 1C drop and indoor cables. Heat shrink sleeve for reinforcement of sheath joint	

Other accessories

# SUMITOMO ELECTRIC INDUSTRIES, LTD.

Tokyo (Japan)

Sumitomo Electric Industries, Ltd.

Akasaka Center Building, 1-3-13, Motoakasaka,  
Minato-ku, Tokyo, 107-8468, JAPAN  
TEL: +81-3-6406-2666  
<http://global-sei.com/sumitomo-electric-splicers>

London (U.K.)

Sumitomo Electric Europe Ltd.

220 Centennial Park, Centennial Avenue, Elstree,  
Herts. WD6 3SL, U.K.  
TEL: +44 20-8953-8118  
<http://www.sumielectric.com/>

Dubai (U.A.E.)

Middle east office

Dubai Airport Free Zone Phase 4WA,  
Office 702 P.O. Box 54890, Dubai, UAE  
TEL: +971 4-701-7338